

R2

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 59-208066

(43)Date of publication of application : 26.11.1984

(51)Int.Cl.

C23C 11/14

C22F 1/18

// C22C 27/04

(21)Application number : 58-082551

(71)Applicant : TOSHIBA CORP

YANO SHINZO

MOROZUMI SHIYOUTAROU

(22)Date of filing : 13.05.1983

(72)Inventor : YANO SHINZO

MOROZUMI SHIYOUTAROU

(54) METHOD FOR WORKING INTERNALLY NITRIDED MOLYBDENUM-ZIRCONIUM ALLOY

(57)Abstract:

PURPOSE: To obtain an Mo alloy with high strength at high temp. and superior workability by forming an Mo-Zr alloy contg. a specified amount of Zr and by internally nitriding the Mo-Zr alloy.

CONSTITUTION: An Mo-Zr alloy contg. 0.01W1.0wt% Zr is worked at about 700W 1,000° C, and the Mo-Zr alloy is internally nitrided to obtain an Mo-Zr alloy with high strength such as high tensile strength or hardness at about 1,000W1,800° C high temp. When the internal nitriding temp. is \leq about 1,350° C, an Mo-Zr alloy with relatively high hardness is obtd., and when the internal nitriding temp. is \geq about 1,350° C, an Mo-Zr alloy with high toughness and tensile strength is obtd.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]